

GD-1602S


1.6m Sublimation Printer (With 2 Heads)



GRANDO Sublimation Ink



Two i3200/4720 Heads



* 1.6m Dual i3200/4720 Print Heads Speed


720x1200dpi - 4pass 40 m²/h

720x1800dpi - 6pass 27 m²/h

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering: top performant, reliable and precise. With Grando series printer, you can maximize production while controlling quality and minimizing costs for beautiful soft signage, apparel and interior decor items that will set your business apart from the competition. Wide applications in clothing, home decoration fabrics, sampling, shirt, canvas bags, bolster, scooter, flags, textile gadgets etc.



Intelligent inkjet printing technology and variable dot ensure the perfect printing output, greatly improve the printing speed, and meet the user's requirements for printing quality and speed.



High speed micro piezoelectric inkjet printing technology GD-1602 TX is equipped with dual i3200/4720 print heads. It adopts advanced board control technology and industrial level design to ensure the durability of the print head.



● Technical Specifications

Model	GD-1602 TX
Print Head	Dual i3200/4720 Print Heads
Printing Technology	Piezoelectric Inkjet
Width	63.8 in.(1620 mm)
Acceptable Media Thickness	Maximum 39 mil(1 mm)
Weight	132.2 lb.(60 kg)
Printing Width	63 in.(1600 mm)
Ink Cartridges Type	Sublimation Ink
Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank)
Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 2400 dpi
Printing Speed	4pass(720x1200dpi): 40sqm/h 6pass(720x1800dpi): 27 sqm/h
Media Heating System	Integrated post heater & Infrared Dryer & Fan system
Interface	LAN
Power Supply	AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)	119(W)x41(D)x56(H) in. (3010(W)x1048(D)x1420(H) mm)
Weight(with stand)	661 lb. (300 kg)
Package Dimensions	124(W)x41(D)x59(H) in. (3140(W)x1048(D)x1490(H) mm)
Package Weight	771 lb. (350 kg)
Environment	Power on Temperature: 59 ™ to 90 ™ [15 ™ to 32 ™] (68 ™ [20 ™] / Humidity: 35 to 80% (no condensation) Power off Temperature: 41 ™ to 104 ™ [5 ™ to 40 ™] / Humidity: 20 to 80% (no condensation)
Accessories	Dual i3200 Print Heads, USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.



THK high-precision mute rail.



New pinch roller structure of three in group brings more stable feeding precision.



High-precision and high-stability tensioning pulley system.



High quality DC servo motor with good stability and long life.



Stable Bulk System Ensures Amazing Printing Speed



Infrared heater and cooling fan.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



External power supply, intelligent rolling system